

# AdvaBond® 7200

## Product Overview

AdvaBond® 7200 is a waterborne, chlorinated, maleic anhydride modified polyolefin adhesion promoter for low surface energy substrates. It is designed to work on surfaces without any surface treatment such as corona or flame. Ideal additive for single-ply membrane roofing adhesive formulations.

## Physical Properties

SOLIDS CONTENT, %:	30%
COLOR & APPEARANCE:	Milky Tan Emulsion
CARRIER SOLVENT:	Water
PH:	7
SPECIFIC GRAVITY (@ 25 C):	1.00
VOC:	<0.5%

## Applications

- Superior adhesion to TPO, PP/EPDM without pre-treatment.
- Excellent additive for lower temperature curing conditions.
- Can be used as a primer or additive.
- Compatible with various waterborne systems.

## Packaging

Available in 8 oz. samples sizes and drum and tote quantities.

## Application Methods

If used as a primer:

Dilute product in water at 1-10% based on actives.

Make sure surface is free of any contamination (dirt, oil, grease or others)

Apply dilution via spray, brush or rod ensuring good coverage.

Apply top coat or adhesive once substrate is dry.

If used as an additive:

Add product in system at 1-10% based on a weight basis depending on performance and/or cost requirements.

Make sure AdvaBond® 7200 is compatible in the system.

Apply adhesive as per required rates and application

ADVANCED POLYMER  
400 Paterson Plank Road  
Carlstadt, NJ 07072