

TECHNICAL DATA SHEET

AdvaBond® 7308

Product Overview

AdvaBond® 7308 is a water-borne adhesion promoter for low surface energy substrates. AdvaBond® 7308 can be used as a primer, additive, or a co-resin to coatings or adhesive formulations for paper, foil or film applications.

Physical Properties

COLOR & APPEARANCE: Tan Liquid

SOLIDS CONTENT, %: 32.5%

PH: 9-10

SPECIFIC GRAVITY (@25 C): 1.0

Applications

- Superior adhesion to various low surface energy substrates
- Low curing temperature
- Compatible with various waterborne resins

Packaging

Available in 8 oz. samples sizes or tote and drum quantities.

Application Methods

If used as a primer:

Dilute down in water at 5-10% on a weight basis. Other additives such as wetting aides or defoamer may be required. Apply via brush, roll, spray or other methods.

If used as an additive/co-resin:

Depending on the system and performance/cost requirements, AdvaBond® 7308 can be used 5-50% on a weight basis. Always check for compatibility with other components in the formulation. Other additives such as wetting aides or defoamer may be required. Apply via brush, roll, spray or other methods.

ADVANCED POLYMER 400 Paterson Plank Road

Carlstadt, NJ 07072

ADVPOLYMER.COM PHONE: 201.933.0600 FAX: 201.933.8442