

AdvaBond® 7485

Product Overview

AdvaBond® 7485 is a water-free adhesion promoter for various low surface energy substrates. AdvaBond®7485 can be used as a primer or as an additive to coating or adhesive formulations. AdvaBond® 7485 can be used in one-component (1K) and two-component (2K) systems to meet the diverse needs of applications.

Physical Properties

| | |
|----------------------------|---------------------------|
| COLOR & APPEARANCE: | Clear to Yellowish Liquid |
| ACTIVES: | >99.0% |
| IONIC PROPERTY: | Cationic |
| SPECIFIC GRAVITY (@ 25 C): | 1.05 |

Applications

- Superior adhesion to various low surface energy substrates
- Miscible in water and other solvent systems
- Compatible with various resin systems

Packaging

Available in 8 oz. samples sizes and drums quantities.

Application Methods

AdvaBond® 7485 is ideal for use in coatings and adhesives where acrylics, urethanes and epoxy systems are utilized.

If used as a primer: 1. Dilute AdvaBond® 7485 with appropriate solvent to 2-10% by weight. 2. Apply primer via brush, roll or spray onto surface. 3. Let dry in room temperature or heat until surface is dry. 4. Apply top coat or adhesive as needed.

If used as an additive: 1. Add product into the coating or adhesive formulation at 2-10% level. 2. Make sure AdvaBond® 7485 is compatible in the system added to. 3. Apply coating or adhesive formulation onto substrate.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072

ADVPOLYMER.COM

PHONE: 201.933.0600

FAX: 201.933.8442

The information set forth herein is furnished free of charge and based on technical data that Advanced Polymer believes to be reliable. It is intended for use by persons having technical skill at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assure no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.