

AdvaBond® 7608

Product Overview

AdvaBond® 7608 is a water-based high solids acrylic emulsion primer designed to help topcoats adhere to low energy substrates commonly used in roofing such as TPO and EPDM rubber.

Physical Properties

COLOR & APPEARANCE:	White-Yellow Liquid
ACTIVE CONTENT:	58%
PH:	7.6
SPECIFIC GRAVITY:	1.03

Applications

- Improves adhesion of topcoats to a variety of roofing sunstrates such as TPO, EPDM, metal, and asphalt.

Packaging

Available in 8 oz. samples sizes, tote and drum quantities.

Application Methods

AdvaBond® 7608 can be rolled or brushed onto the roofing surface in an even layer. Allow the primer to cure at least 2 to 4 hours before applying topcoat. Cured primer will be tacky to the touch which aids in adherence of the applied topcoat.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072

ADVPOLYMER.COM

PHONE: 201.933.0600

FAX: 201.933.8442

The information set forth herein is furnished free of charge and based on technical data that Advanced Polymer believes to be reliable. It is intended for use by persons having technical skill at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assure no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.