

AdvaBond® 8205

Product Overview

AdvaBond® 8205 is a chlorinated polyolefin based adhesion promoter that provides excellent adhesion to low surface energy substrates, especially PP, TPO and EPDM. AdvaBond® 8205 can be used as a primer or as an additive to an ink, coating, paint or adhesive formulation.

Physical Properties

APPEARANCE:	Amber Solution
SOLID CONTENT:	57%
CARRIER SOLVENT: SPECIFIC	Xylene
GRAVITY:	1.01

Applications

- Superior adhesion to PP, TPO or EPDM and other low surface energy substrates.
- High solids, easy formulation.
- Compatible with a variety of different resins.
- Can be used as primer or as an additive.

Packaging

Available in 8 oz. samples sizes and 397-lb drum quantities.

Application Methods

If used as a primer:

- Dilute product in solvent at 1-10% based on actives.
- Make sure surface is free of any contamination (dirt, oil, grease or others)
- Apply dilution via spray, brush or rod ensuring good coverage.
- Apply top coat or adhesive once substrate is dry.

If used as an additive:

- Add product in system at 1-10% based on a weight basis depending on performance and/or cost requirements.
- Make sure AdvaBond® 8205 is compatible with the system.
- Apply coating or adhesive as per required rates and application.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072