

### TECHNICAL DATA SHEET

# AdvaBond<sup>®</sup> 8227

#### **Product Overview**

AdvaBond<sup>®</sup> 8227 is a modified chlorinated polyolefin adhesion promoter for PP, TPO, EPDM and other polypropylene containing substrates without pre-treatment. The product has a great compatibility with various solvents and other resins.

## **Physical Properties**

APPEARANCE:	Yellowish
PRODUCT FORM:	Liquid
SOLVENT:	N-Butyl Acetate/Cyclohexane
RESIN CONTENT:	30%

#### **Applications**

- Superior adhesion to low surface energy materials like, PP, EPDM, Tyvek, recycled plastic, and TPO.
- Transparent film after coating and drying.
- Very good compatibility with various solvents and other resins.
- Can be used as an additive to various solvent borne adhesives and primers.

#### Packaging

Available in 8 oz. samples and drums.

#### **Application Methods**

When using AdvaBond<sup>®</sup> 8227 as a primer, dilute down to 1—10% actives solution. Apply a thin layer onto substrate. Let dry for 1—3 minutes prior to application of other paints, coatings or adhesives.

When using AdvaBond® 8227 as an additive, use 1-10% on a total weight basis. System compatibility should be checked

and a ladder study of the additive should be tested in order to determine the optimum level for your application.

#### ADVANCED POLYMER 400 Paterson Plank Road

Carlstadt, NJ 07072

#### ADVPOLYMER.COM

PHONE: 201.933.0600

FAX: 201.933.8442

The information set forth herein is furnished free of charge and based on technical data that Advanced Polymer believes to be reliable. It is intended for use by persons having technical skill at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assure no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.