

ProvectuPel® 753

Product Overview

ProvectuPel® 753 is a waterborne, fluorine-free penetrating sealer that is designed to seal and protect various hard surfaces, including natural stone, tile, slate and grout. ProvectuPel® 753 leaves an invisible barrier coating that protects surfaces from water.

Physical Properties

APPEARANCE:	Milky White Liquid
ACTIVE CONTENT:	50%
PH:	6.5
CARRIER SOLVENT:	Water
SPECIFIC GRAVITY (@ 25 C):	1.00

Applications

- Fluorine (PFAs) free chemistry
- Effective at low concentrations
- Excellent water repellency
- Fit for various surfaces
- Long lasting properties

Packaging

Available in 8 oz. samples sizes, drums and totes.

Application Methods

Sample Formulation:

ProvectuPel® 753 can be diluted in soft and/or DI water. Depending on performance and cost requirements, it can be diluted at 1—5% solids. Other additives such as wetting aids and/or defoamers may be required for improved properties onto the surface.

Application Condition:

ProvectuPel® 753 may be applied using a saturated brush, roller, mop, or low pressure garden-type sprayer. Dry and cure for a minimum of 24 hours before testing.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072