

ProvectuPel® 765

Product Overview

ProvectuPel® 765 is a waterborne, fluorine-free penetrating sealer designed to seal and protect various hard surfaces, such as, natural stone, tile, grout and many more. ProvectuPel® 765 leaves an invisible barrier coating that protects surfaces from water and water-based stains.

Physical Properties

APPEARANCE:	Milky White Liquid
SPECIFIC GRAVITY (25°C):	1.05
ACTIVITY (%):	40%
SOLVENT:	Water
pH:	11

Applications

Used to seal and protect natural stone, grout, tile from water and stain.

Will not change the appearance of the treated substrate.

Packaging

ProvectuPel®765 is available in 8 oz. samples and 441-lb drums.

Application Methods

ProvectuPel® 765 can be diluted in soft and/or DI water at 1–5% solids (4 – 20% on a weight basis). Additives such as wetting aids and/or defoamers may be required for improved properties onto the surface.

ProvectuPel® 765 may be applied using a saturated brush, roller, mop, or low pressure garden-type sprayer. Dry and cure for a minimum of 24 hours before testing.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072

ADVPOLYMER.COM

PHONE: 201.933.0600

FAX: 201.933.8442

The information set forth herein is furnished free of charge and based on technical data that Advanced Polymer believes to be reliable. It is intended for use by persons having technical skill at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assure no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.