

### TECHNICAL DATA SHEET

# ProvectuPel®782

#### **Product Overview**

ProvectuPel® 782 is a waterborne, fluorine-free durable water repellent finish for various textiles, from natural to synthetic fibers. ProvectuPel® 782 is suitable for various sealant applications where stain and water repellency is desired.

## Physical Properties

APPEARANCE: Clear Liquid

SPECIFIC GRAVITY (25°C): 1.00

ACTI VITY (%): ~17.0%

SOLVENT: Water

pH: ~7.0

#### **Applications**

- Water proofing for fabric
- Fluorine (PFAs) free
- Effective at low concentrations
- Stain release
- Ambient cure

#### **Packaging**

ProvectuPel® 782 is available in 8 oz. samples and 441-lb drums.

### **Application Methods**

ProvectuPel® 782 can be diluted in DiWater to 1.0—2.0% actives (5 - 10% on a weight basis).

Additives such as wetting aids and/or defoamers may be required for improved properties onto the surface.

ProvectuPel® 782 may be applied with padding machine or low pressure sprayer. Product will cure at both ambient and oven (163C for 5 minutes) temperatures.

#### ADVANCED POLYMER

400 Paterson Plank Road Carlstadt, NJ 07072

ADVPOLYMER.COM PHONE: 201.933.0600 FAX: 201.933.8442