

ProvectuPel® 810

Product Overview

ProvectuPel®810 is a reactive silicone resin designed to produce a durable, super-hydrophobic surface when applied to various substrates.

Physical Properties

APPEARANCE:	Clear Liquid
SPECIFIC GRAVITY (25°C):	0.822
ACTIVITY (%)	50%
SOLVENT:	D4
% VOC:	-3.0

Applications

- Superhydrophobic properties on various substrates: textiles, stones, plastics, auto/marine surfaces
- Excellent durability.
- Will not change the appearance of the treated substrate.

Packaging

ProvectuPel®810 is available in 8 oz. samples and 419-lb drums.

Application Methods

ProvectuPel®810 is to be diluted with Isopar G (odorless mineral spirits) 2.5% and 3.0% actives (5% to 6% as supplied) applied via brush or pump spray.

The treated substrates should dry/cure for at least 24 hours. The curing stage can take longer than 24 hours, which will only improve the products performance.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072

ADVPOLYMER.COM

PHONE: 201.933.0600

FAX: 201.933.8442

The information set forth herein is furnished free of charge and based on technical data that Advanced Polymer believes to be reliable. It is intended for use by persons having technical skill at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assure no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.