

ProvectuPel® 755

Product Overview

ProvectuPel® 755 is a waterborne, fluorine-free penetrating sealer that is designed to seal and protect various hard surfaces, including natural stone, tile, slate and grout. ProvectuPel® 755 leaves an invisible barrier coating that protects surfaces from water and water-based stains.

Physical Properties

APPEARANCE:	Milky white, emulsion
SOLID CONTENT:	25.0%
PH:	6.0
SPECIFIC GRAVITY:	1.05
CARRIER SOLVENT:	WATER

Applications

- Fluorine (PFAs) free chemistry
- Effective at low concentrations
- Excellent water, and stain repellency
- Fit for various surfaces
- Long lasting properties

Packaging

Available in 8 oz. samples sizes and drums and totes.

Application Methods

Sample Formulation: ProvectuPel® 755 can be diluted in soft and/or DI water. Depending on performance and cost requirements, it can be diluted at 1—5% solids (4 - 20% on a weight basis). Other additives such as wetting aids and/or defoamers may be required for improved properties onto the surface.

Application Condition: ProvectuPel® 755 may be applied using a saturated brush, roller, mop, or low pressure garden-type sprayer. Dry and cure for a minimum of 24 hours before testing.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072