

ProvectuPel® 837-50

Product Overview

ProvectuPel® 837-50 is a solvent borne, non-fluorinated polymer. ProvectuPel® 837-50 can also be used as a penetrating sealer for hard surfaces including porous and dense surfaces such as natural stone, tile, concrete, brick and grout.

Physical Properties

APPEARANCE:	Clear to Amber Liquid
SPECIFIC GRAVITY (@25C):	~0.85
SOLID CONTENT:	22%
CARRIER SOLVENT:	Odorless Mineral Spirits

Applications

- Short chain, PFOA free fluoropolymer chemistry
- Effective at low concentrations
- Cost effective solution for your protective treatments and penetrating sealers
- Excellent oil hold-out, water, and stain repellency
- Long lasting properties

Packaging

Available in 8 oz. samples sizes and 350 lb. drums.

Application Methods

Sample Formulation:

ProvectuPel® 837-50 can be diluted in a wide range on non-polar solvents. Depending on application and performance requirements, it can easily be diluted in odorless mineral spirits at 1 - 8% solids

ProvectuPel® 837-50 may be applied using a saturated brush, roller, or mop, or low pressure garden-type sprayer. Dry and cure minimum 24 hours before testing.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072