

# AdvaBond® F7444

## Product Overview

AdvaBond® F7444 is a waterborne adhesion promoter designed to be used as an additive for heat-activated adhesives and coatings. AdvaBond® F7444 provides superior adhesion to various low surface energy substrates.

## Physical Properties

APPEARANCE:	Translucent Liquid
ACTIVE CONTENT:	30.0
PH:	9.5
CARRIER SOLVENT:	Water
SPECIFIC GRAVITY:	1.00

## Applications

- Superior adhesion to PP and other low surface energy surfaces.
- Low-medium activation temperature
- Transparent film after coating and drying.
- Compatible with various waterborne systems.
- Provides some heat and humidity resistance.
- Complies with 21.CFR 175.105

## Packaging

Available in 8 oz. samples sizes and drum quantities.

## Application Methods

AdvaBond® F7444 can be added into the system at 1-10wt% of the total formulation. It can be formulated to perform on various substrates and at specific adhesion values. Additives for wetting, block resistance and defoaming may be needed to achieve coating properties.

Final formulated system can be used in gravure, flexographic, roll, rod and other coating applications.

ADVANCED POLYMER  
400 Paterson Plank Road  
Carlstadt, NJ 07072

ADVPOLYMER.COM

PHONE: 201.933.0600

FAX: 201.933.8442

The information set forth herein is furnished free of charge and based on technical data that Advanced Polymer believes to be reliable. It is intended for use by persons having technical skill at their own risk. Because conditions of use are outside our control, we make no warranties, express or implied, and assure no liability in connection with any use of this information. Nothing herein is to be taken as license to operate under or a recommendation to infringe any patents.