

Product Overview

APS-219 is a methyl hydrogen polysiloxane fluid that cures to a dry highly hydrophobic film. Due to its unique functionality, APS-219 will provide superior performance.

Physical Properties

APPEARANCE:	Milky White Emulsion
SOLID CONTENT:	50%
SPECIFIC GRAVITY:	0.98
PH:	6.0

Applications

- Imparts superior water repellency.
- Self curing polymer.
- Non-flammable.

Packaging

Available in 8 oz samples and 441 lb drums.

Application Methods

- Suitable for power treatment.
- Water repellent for glass and textiles.

IMPORTANT NOTE: APS-219 must be kept away from moisture. Diluents used with APS-219 must have a moisture content less than 50ppm. If APS-219 is exposed to a high concentration of moisture, the evolution of gas will occur.

STORAGE & HANDLING

Stored in a sealed container at temperatures between 5°C and 30°C, APS-219 has a prolonged shelf life.

Special considerations:

Keep container closed when not in use. Vent the container properly to eliminate internal pressure. Store in a cool place away from heat, sparks and flame. Do not lay the container on its side. Avoid contact with eyes and prolonged or repeated contact with skin. Avoid contact with acidic, basic or oxidizing materials. Keep out of reach of children.

Handling of Empty Container:

Do not re-use this container. Keep away from heat, sparks and flame. Do not puncture or cut this container. Do not weld near this container.

ADVANCED POLYMER
400 Paterson Plank Road
Carlstadt, NJ 07072